

Model DR-2



Control 2 PCs from One Monitor / Mouse / Keyboard



FEATURES

- Works with all VGA Monitor Types
- Convenient Desktop Size
- Embedded Mouse Translation for Serial Mouse
- 1280 x 1024 Video Resolution
- AutoBoot Capability



DESCRIPTION

Gets that Second Keyboard, Monitor & Mouse off your Desk

The Model DR-2 was created for the busy desktop. The Duette Commander fills the bill for a simple, cost effective switch. Free up needed space on your desk by eliminating one set of peripherals. Your computers can be as far as 30 feet away from the Commander, so you have lots of freedom insetting up your work area.

Easy to Install, Easier to Use

With the Duette Commander, there is no software to install. There are no boards to configure or networks to run. Just connect your computers to the Duette Commander and you are ready to work. With the Duette's AutoBoot capability, both computers will boot automatically after powering up so your PCs are always ready as soon as you are.

Two Ways to Switch for Fast, Convenient Operation

You can switch between your attached computers smoothly and easily using the push-buttons on the Duette's front panel. If the Duette is out of reach, a simple keyboard sequence will change your active computer as well.

The System

A Duette Commander system consists of a Duette Commander Unit (Model DR-2) and a 6, 8, 15, or 30-foot cable assembly for each attached computer (Model CUFC-x). The cables are universal supporting both Serial / PS/2 mouse and 5-pin / PS/2 keyboard on the attached computers. The Duette Commander requires a PS/2 mouse and either a PS/2 or 5-pin keyboard. For compatibility with your installed equipment, the Duette Commander features an embedded mouse translation capability. Operated through the Duette Commander, your PS/2 mouse will work with any attached PC or server regardless of whether the computer has a PS/2 or serial mouse.

The Duette can be powered by the keyboards of the attached computers. If separate power is preferred, optional wall transformer units are available for either 110VAC or 220VAC.

SPECIFICATIONS

Number of Channels

2

Supported Hardware

Computer: PC/AT, PS/2 and 100% compatible
Video Modes: VGA, SVGA
Maximum Resolution: 1280 x 1024 @ 60Hz
Peripherals: PS/2 keyboard & mouse

Mouse Compatibility

IBM PS/2 Style
Kensington
Logitech Mouseman (PS/2)
Logitech Trackman
Microsoft Serial-PS/2 mouse
(Others might work, but these are known to be compatible)

Operating Voltage

6VDC

Temperature

Operating: 5°C to 40°C
Storage: -20°C to 50°C

Size

Height: 2.69" (68.3mm)
Width: 7.13" (181.1mm)
Depth: 4.94" (125.5mm)

Agency Approvals

UL 1950
CSA C22.2 No. 950
EN 60950
EN 55022
EN 50082
FCC Part 15B

ORDERING GUIDE

Model DR-2

Standard unit, no on-screen display, manual, power cord

WALL TRANSFORMERS (OPTIONAL)

Model 038-0027

110VAC in, 6VDC out

Model 038-0039

220VAC in, 6VDC out

CABLES

Model CUFC-6

6 ft cable

Model CUFC-8

8 ft cable

Model CUFC-15

15 ft cable

Model CUFC-30

30 ft cable



INDUSTRIAL COMPUTER SOURCE®

6260 Sequence Drive, San Diego, CA 92121

1-800-523-2320
<http://www.indcomsrc.com>